

PRODUCT INFO

Desktop Power Supply with Selectable Output

LI 0055 - 35W

LI 9935 - 50W

Output voltage 5-24V is selected
by a changeable slot

FEATURES

- Universal Input voltage
- Selectable output voltages
- Over voltage protected
- Over load protected
- Over heat protected



	LI 0055	LI 9935
Input Insulation Class II	100-240Vac	100-240Vac
Output:	5V/4,0A 6V/3,5A 7V/3,3A 8V/3,2A 9V/3,0A 10V/2,8A 11V/2,6A 12V/2,5A 13V/2,4A 14V/2,3A 15V/2,2A 16V/2,1A 17V/2,0A 18V/1,9A 19V/1,8A 20V/1,7A 21V/1,6A 22V/1,6A 23V/1,5A 24V/1,5A	5V/5,0A 6V/4,5A 7V/4,3A 8V/4,2A 9V/4,0A 10V/3,8A 11V/3,8A 12V/3,8A 13V/3,5A 14V/3,3A 15V/3,1A 16V/2,8A 17V/2,7A 18V/2,6A 19V/2,4A 20V/2,3A 21V/2,2A 22V/2,1A 23V/2,0A 24V/1,9A
Output Connectors:	5,5/2,1 5,5/2,5 5;0/2,1 4,0/1,7 3,5/1,2 3/1,0 2,35 /0,7 3,5 & 2,4mm	
Temp. Range:	0 to +40°C	0 to +40°C
Safety Standards:	EN60950/UL1950	EN60950/UL1950
Dimensions:	90 x 45 x 29 mm	108 x 56 x 37 mm
Weight:	195 g	265 g

Machatka

Heuberggasse 5

Tel: +43 / 1 / 888 38 04

christian.machatka@aon.at

Power Supplies

A-1130 Vienna

Fax: 888 15 00

www.machatka.at